



Ideal for working plaster-board, gypsum fibre boards and wooden boards

New

BeA Skater with BeA 180/65-835C

BeA Skater is equipped with the tried-and-trusted BeA tool 180/65-835C

2-man operation for board widths up to 3 m

- Modern safety functions protect both the operator and the workpiece
- Both handles with safety yoke
- Safety yoke on the board
- Dry-firing lock
- Quick-release
- Rotatable waste air cover

Optimum working result in compliance with Eurocode 5

- Staple angle 30° in compliance with EC 5
- Stepless height adjustment
- Single shots always possible
- Location grooves for precise work on the centre of the board
- Wheels are non-marking

Flexible re-tooling for different requirements

- The tool on the Skater can be replaced within 20 seconds

Applications

Timber frame constructions, pre-fabricated housing and all other applications where plasterboard, gypsum board and wooden boards (e.g. OSB panels) are fitted/worked.



BeA Skater with BeA 180/65-835C

Technical Data



BeA Skater

Article code	14412430
EAN code	4045759695974

BeA 14/65-830C

Article code	12000625
EAN code	4045759056850
Magazine type	Top loader
Weight [incl.Skater]	11.8 kg
Dimensions in mm [incl. Skater, L/W/H]	553 mm / 345 mm / 326 mm
Safety system	Path controlled contact actuation
Fastener type	Type 180 (15 gauge)
Magazine capacity	Min. 132 staples
Fasteners per strip	2 x 60 (VZ HZ 3 x 40)
Operating pressure	6 – 8 bar (90 – 120 psi)
Max operating pressure	8 bar (120 psi)
Air consumption /operation	2.9 litre / 6 bar
Inner hose diameter	Ø 9 – 10 mm recommended
Emission sound pressure level at the work station	L _{pA, 1s, d} = 82.0 dB
Single shot emission sound pressure level	L _{WA, 1s, d} = 89.0 dB
Vibration level as per ISO 8662-11 is	3.2 m/s ²
Accessories supplied with the tool	Operating instructions, spare parts list, service instructions, allen wrenches

Subject to technical modifications

Optional accessories:



Edge guide
[Art. code 14412428]

Extension handle
[Art. code 14412429]



Rail
[Art. code 14406482
resp. 14409063,
without picture]

Staples Type 180



Description	L = Length (mm)
180/40 NK HZ	40
180/45 NK HZ	45
180/50 NK HZ	50
180/55 NK HZ	55
180/60 NK HZ	60
180/63 NK HZ	63
180/65 NK HZ	65

Staples type 180 are available in VZ HZ (service class 2) and NR HZ (service class 3) and certified to DIN 1052

Joh. Friedrich Behrens AG
Industrial Fastening Systems
Bogenstrasse 43 – 45
22926 Ahrensburg
Germany

For further information:
Phone: + 49(0) 41 02 78 - 444
Fax + 49 (0) 41 02 78 - 270
eMail: info@bea-group.com
www.Bea-Group.com

BeA is a member of the following associations:

